

SERIE EFF

Fix - Smasher



La serie di **FRANTUMATORI FISSI EFF** sono espressamente realizzati per consentire una rapida demolizione a terra, riducendo quello che si trova già a terra: le fasi di carico e trasporto saranno semplificate, aumentando il risparmio dell'utilizzatore.

- Innovativo sistema di valvola "PRESSURE RELIEF"
- Valvola auto frizionante in rotazione
- Cilindri rovesciati e protetti
- Valvole di velocità
- Struttura anti-usura
- Denti intercambiabili
- Lame intercambiabili



EFF Fix Pulveriser are specifically to crumble quickly apart parts already on ground: loading and transport will be easier and faster, giving the opportunity to save money by the operator



- Innovative "PRESSURE RELIEF VALVE"
- Auto frictioning Rotation valve
- Reversed cylinder to protect the rod
- Fast valve
- Anti-wear body
- Interchangeable teeth
- Interchangeable blades

SERIE EFF

Fix-Smasher

HARDOX®
IN MY BODY

MODEL		EFF5	EFF11	EFF16	EFF21	EFF28	EFF45	EFF49	EFF104
Apertura Opening	mm	510	700	820	860	1050	1080	1150	1800
Lunghezza Length	mm	1300	1900	2100	2300	2650	2700	2800	3200
Larghezza Width	mm	330	400	460	550	560	600	760	950
Lama Blade	mm	140	160	200	200	240	240	240	300
Peso Escavatore Excavator Weight	T	6/10	10/16	15/20	21/29	30/45	40/60	60/80	80/130
Peso Weight	Kg	500	1100	1650	2100	2850	4550	4900	10600
Forza Dente Teeth Force	T	135	170	200	250	340	450	500	550
Forza Lama Blade Force	T	35	60	75	90	120	145	170	235
Pressione Olio Pressure Oil	Bar	250	300	320	320	320	340	340	340
Portata Olio Oil Capacity	L/ min	80/100	180/220	200/240	250/300	250/300	300/350	400/450	500/550

